## NSN 3020-00-124-1499

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-124-1499

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 1.7490 inches and 1.7500 inches
Teeth Quantity:
84
Bore Style:
Plain both ends
Mounting Hole Type And Quantity:
1 plain transversely through hub, first end
Outside Diameter:
1.791 inches
Nominallength:
0.437 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.188 inches
Bore Diameter:
0.250 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.505 inches first end
0.505 inches first end  Precision Classification:
Precision Classification:
Precision Classification: Quality number 10
Precision Classification: Quality number 10 Mounting Hole Diameter:
Precision Classification: Quality number 10  Mounting Hole Diameter: 0.077 inches axially through flange and 0.081 inches axially through flange
Precision Classification: Quality number 10  Mounting Hole Diameter: 0.077 inches axially through flange and 0.081 inches axially through flange Material:
Precision Classification: Quality number 10 Mounting Hole Diameter: 0.077 inches axially through flange and 0.081 inches axially through flange Material: Steel comp 303
Precision Classification: Quality number 10  Mounting Hole Diameter: 0.077 inches axially through flange and 0.081 inches axially through flange  Material: Steel comp 303  Surface Treatment:

**Style Designator:** Protruding hub

## NSN 3020-00-124-1499

Spur Gear - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300