NSN 3020-00-127-9579

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-127-9579 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 0.5615 inches and 0.5625 inches **Teeth Quantity:** 27 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.112 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 2 threaded transversely through hub, first end **Outside Diameter:** 0.603 inches **Tooth Form:** Standard **Pressure Angle:** 30.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.225 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.250 inches both ends **Hub Style Designator:** Plain first end **Hub Diameter:** 0.450 inches first end **Precision Classification:** Quality number 10 Material: Aluminum alloy 6061 **Material Specification:** Qq-a-250/11, alloy 6061 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2, class 2 military specification single treatment response

NSN 3020-00-127-9579

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-std (military Standard):

Mil-a-8625 spec.