NSN 3020-00-130-0830

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-130-0830

| Body Style: |
|--|
| Plain, solid |
| Pitch Diameter: |
| 0.2395 inches |
| Teeth Quantity: |
| 23 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 0.260 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.031 inches first end |
| Face Width: |
| 0.406 inches |
| Bore Diameter: |
| 0.094 inches both ends |
| Hub Style Designator: |
| Plain first end |
| Hub Diameter: |
| 0.135 inches first end |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Mil-s-7720, comp 303, cond a military specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

.

A27300

NSN 3020-00-130-0830

Spur Gear - Page 2 of 2



Mil-std (military Standard):

Mil-s-7720 spec.