## NSN 3020-00-130-5989

View Online at https://aerobasegroup.com/nsn/3020-00-130-5989

Spur Gear - Page 1 of 2



Pitch Diameter: 1.0417 inches **Teeth Quantity:** 25 **Outside Diameter:** 1.144 inches **Tooth Form:** Stub **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.335 inches both ends **Face Width:** 1.500 inches **Bore Diameter:** 0.047 inches both ends **Keyway Width:** 0.037 inches both ends **Distance From Bore Center To Keyway Bottom:** 0.329 inches both ends **Counterbore Depth:** 1.465 inches second end **Counterbore Diameter:** 0.675 inches second end **Hub Style Designator:** 1 step both ends **End Length:** 0.260 inches both ends **Precision Classification:** Quality number 9 **End Diameter:** 0.749 inches both ends First Step Length: 0.075 inches both ends First Step Diameter: 0.895 inches both ends **Special Features:** 2 internal keyways spaced 180 degs apart Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/6, t4 federal specification single material response

## **NSN 3020-00-130-5989** Spur Gear - Page 2 of 2

Fiig: A27300



Surface Treatment:
Silver
Surface Treatment Specification:
Ams 2412 assn standard single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli