

NSN 3020-00-130-9526 Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-130-9526

| Body Style: |
|--|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.1250 inches |
| Teeth Quantity: |
| 108 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Thread Series Designator: |
| Unc transversely through hub, first end |
| Mounting Hole Thready Qty Per Inch (tpi): |
| 56 transversely through hub, first end |
| Mounting Hole Thread Size: |
| 0.086 inches transversely through hub, first end |
| Mounting Hole Type And Quantity: |
| 2 threaded transversely through hub, first end |
| Outside Diameter: |
| 1.145 inches |
| Nominallength: |
| 0.171 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.131 inches first end |
| Face Width: |
| 0.040 inches |
| Bore Diameter: |
| 0.090 inches both ends |
| Hub Style Designator: |
| Pinned first end |
| Hub Diameter: |
| 0.312 inches first end |
| |
| Special Features: |
| Special Features: Mtg holes 120 degs apart |
| |
| Mtg holes 120 degs apart |

Mil-s-7720, comp 303, cond a military specification single material response

NSN 3020-00-130-9526

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-s-7720 spec.



| Surface Treatment: |
|---|
| Passivate |
| Surface Treatment Specification: |
| Mil-std-171, finish no. 5.4.1 military standard single treatment response |
| Style Designator: |
| Protruding hub |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |