# NSN 3020-00-132-0935

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-132-0935

Body	Style:
Plain,	solid

Attachment Method:

Mounting hole

Pitch Diameter:

Between 0.3730 inches and 0.3750 inches

**Teeth Quantity:** 

18

Bore Style:

Plain both ends

Mounting Hole Thread Series Designator:

Unc transversely through hub, first end

Mounting Hole Thread Size:

0.112 inches transversely through hub, first end

#### Mounting Hole Type And Quantity:

1 plain transversely through hub, first end and 2 threaded transversely through hub, first end

Outside Diameter:

0.415 inches

Tooth Form:

Standard

**Pressure Angle:** 

14.5000 degrees

#### Distance Between Body Face And Protruding Hub End:

0.250 inches first end

Face Width:

0.187 inches

Bore Diameter:

0.126 inches both ends

Hub Style Designator:

Plain first end

Hub Diameter:

0.312 inches first end

**Precision Classification:** 

Quality number 10

Mounting Hole Diameter:

0.055 inches transversely through hub, first end

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4, t4 federal specification single material response

Surface Treatment:

Anodize

# NSN 3020-00-132-0935

Spur Gear - Page 2 of 2



### Surface Treatment Specification:

Mil-f-14072, finish e511 military specification single treatment response

### Style Designator:

Protruding hub

Shelf Life:

N/a

## Unit Of Measure:

--

### Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.