NSN 3020-00-133-4505

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-133-4505

| Body Style: |
|--|
| Webbed, with lightening holes |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.0000 inches |
| Teeth Quantity: |
| 96 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Type And Quantity: |
| 8 plain axially through flange |
| Outside Diameter: |
| 1.021 inches |
| Tooth Form: |
| Standard |
| Flange Diameter: |
| 1.410 inches |
| Pressure Angle: |
| 20.0000 degrees |
| Flange Thickness: |
| 0.396 inches |
| Face Width: |
| 0.090 inches |
| Bore Diameter: |
| 0.500 inches both ends |
| Distance Between Outer Body Face And Inner Flange Face: |
| 0.544 inches |
| Hub Diameter: |
| 0.620 inches between body and flange |
| Mounting Hole Diameter: |
| 0.210 inches axially through flange |
| Material: |
| Steel comp 303 |
| Material Specification: |
| Mil-s-7720, comp 303, cond a military specification single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Mil-std-171, finish no. 5.4.1 military standard single treatment response |

Style Designator: Flanged end

NSN 3020-00-133-4505

Spur Gear - Page 2 of 2



| Shelf | Life: |
|--------|-------|
| 011011 | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-7720 spec.