## NSN 3020-00-133-8499

Sprocket Wheel - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/3020-00-133-8499

Counterbore Diameter:
1.015 inches
Counterbore Depth:
0.312 inches
Outside Diameter:
Between 2.620 inches and 2.680 inches
Overall Length:
1.125 inches
Keyway Width:
0.188 inches
Bore Diameter:
0.876 inches
Bore Length:
0.532 inches
Distance From Center Of Bore To Bottom Of Keyway:
0.093 inches
Drilled Hole Diameter:
Between 0.193 inches and 0.199 inches
Pitch Diameter:
2.405 inches
Securing Hole Quantity:
1
Face Width:
0.844 inches
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
45.0 rockwell c body and 55.0 rockwell c body
Counterbore Feature:
Included
Counterbore Location:
Aa end
Hole Location:
Through body
Keying Facility:
Included
Keying Facility Type:
Kovavov
Keyway
Securing Method:

## **NSN 3020-00-133-8499** Sprocket Wheel - Page 2 of 3



Lightening Hole:
Not included
Protruding Hub Characteristic: Plain
· · ·
Securing Location:
Bb end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Double roller
Teeth Row Quantity:
2
Center To Center Distance Between Teeth Rows:
0.566 inches
Teeth Quantity Per Row:
15
Asa Standard Chain Number:
40-2
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 45.0 rockwell c and 55.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.500 inches
Hub End Outside Diameter And Location:
1.812 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.281 inches aa end
Material:
Steel, aisi c1040
Material:
Steel comp 1040
Material Specification:
Aisi c1040 assn standard single material response
Quantity:
1
Surface Treatment:
Phosphate
Style Designator:

Plain

## NSN 3020-00-133-8499

Sprocket Wheel - Page 3 of 3



Surface Treatment
-------------------

Phosphate coating, mil-p-16232, ty m, cl 1, w/mil-l-644 oil treatment

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

T353-c