

View Online at <https://aerobasegroup.com/nsn/3020-00-134-7946>

**Groove Depth:**

0.560 inches

**Groove Width:**

0.515 inches

**Outside Diameter:**

Between 8.790 inches and 8.810 inches

**Overall Length:**

1.420 inches

**Keyway Width:**

Between 0.126 inches and 0.128 inches

**Thread Size:**

3/8-16

**Bore Diameter:**

Between 0.670 inches and 0.671 inches

**Bore Length:**

1.100 inches

**Distance From Center Of Bore To Bottom Of Keyway:**

0.405 inches

**V Groove Angle In Deg:**

36.0

**Securing Hole Quantity:**

3

**Material And Location:**

Iron, qq-i-652-canceled

**Face Width:**

1.420 inches

**Design Form:**

Webbed

**Bore Type:**

Straight

**Bearings:**

Not included

**Groove Quantity:**

2

**Counterbore Feature:**

Not included

**Hole Location:**

Through pulley body, 120 degrees apart, 4.360 in. Diameter bc

**Keying Facility:**

Included

**Keying Facility Type:**

Keyway

**Securing Method:**

Threaded hole

**Split Hub Feature:**

Not included

**Web/spoke Relationship To Face Centerline:**

Offset

**Lightening Hole:**

Included

**Integral Cooling Vane:**

Not included

**Groove Shape:**

V

**Bore Feature:**

Included

**Protruding Hub Characteristic:**

Plain

**Securing Location:**

Both ends

**Hub End Outside Diameter And Location:**

1.180 inches aa end and 1.240 inches bb end

**Distance From Outside Flange/rim To Hub End And Location:**

0.620 inches bb end

**Quantity:**

1

**Surface Treatment:**

Enamel

**Style Designator:**

Webbed or spoked

**Surface Treatment:**

Enamel, baked

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T353-a