

View Online at <https://aerobasegroup.com/nsn/3020-00-134-7946>

Groove Depth:

0.560 inches

Groove Width:

0.515 inches

Outside Diameter:

Between 8.790 inches and 8.810 inches

Overall Length:

1.420 inches

Keyway Width:

Between 0.126 inches and 0.128 inches

Thread Size:

3/8-16

Bore Diameter:

Between 0.670 inches and 0.671 inches

Bore Length:

1.100 inches

Distance From Center Of Bore To Bottom Of Keyway:

0.405 inches

V Groove Angle In Deg:

36.0

Securing Hole Quantity:

3

Material And Location:

Iron, qq-i-652-canceled

Face Width:

1.420 inches

Design Form:

Webbed

Bore Type:

Straight

Bearings:

Not included

Groove Quantity:

2

Counterbore Feature:

Not included

Hole Location:

Through pulley body, 120 degrees apart, 4.360 in. Diameter bc

Keying Facility:

Included

Keying Facility Type:

Keyway

Securing Method:

Threaded hole

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Bore Feature:

Included

Protruding Hub Characteristic:

Plain

Securing Location:

Both ends

Hub End Outside Diameter And Location:

1.180 inches aa end and 1.240 inches bb end

Distance From Outside Flange/rim To Hub End And Location:

0.620 inches bb end

Quantity:

1

Surface Treatment:

Enamel

Style Designator:

Webbed or spoked

Surface Treatment:

Enamel, baked

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a