## NSN 3020-00-135-1576

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-135-1576

Outside Diameter:

4.0000 inches
Overall Length:
0.750 inches
Keyway Width:
0.188 inches
Bore Diameter:
0.625 inches
Bore Length:
0.750 inches
Distance From Center Of Bore To Bottom Of Keyway:
0.395 inches
Pitch Diameter:
3.245 inches
Face Width:
0.250 inches
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
38.0 rockwell c body and 43.0 rockwell c body
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Keyway
Securing Method:
Key
Lightening Hole:
Not included
Protruding Hub Characteristic:
Plain
Securing Location:
Both ends
Teeth Row Quantity:
1
Teeth Quantity Per Row:
6
Hardness Rating Test Method:
Rockwell

## **NSN 3020-00-135-1576** Sprocket Wheel - Page 2 of 2



Teeth Hardness Rating:
Detuces 00.0 and and 10.0 and 10.0 and 10.0
Between 38.0 rockwell c and 43.0 rockwell c
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.5408 inches
Hub End Outside Diameter And Location:
1.250 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.500 inches aa end
Material:
Steel, carbon
Material:
Steel
Quantity:
1
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c