NSN 3020-00-135-9343

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-135-9343

Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.0937 inches
Teeth Quantity:
70
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
56 transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
1.125 inches
Nominallength:
0.312 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.187 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.125 inches both ends
Hub Diameter:
0.312 inches first end
Precision Classification:
Quality number 10 or quality number 11
Quality number 10 or quality number 11 Material:
Material:
Material: Steel comp 303
Material: Steel comp 303 Material Specification:
Material: Steel comp 303 Material Specification: Aisi 303 assn standard single material response
Material: Steel comp 303 Material Specification: Aisi 303 assn standard single material response Surface Treatment:
Material: Steel comp 303 Material Specification: Aisi 303 assn standard single material response Surface Treatment: Passivate
Material: Steel comp 303 Material Specification: Aisi 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Material: Steel comp 303 Material Specification: Aisi 303 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-s-5002 military specification single treatment response

NSN 3020-00-135-9343

Spur Gear - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-s-5002 spec.

A27300

Shelf Life: