## NSN 3020-00-136-1203

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-136-1203

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Serration Quantity:
16 both ends
Pitch Diameter:
4.1000 inches
Teeth Quantity:
41
Bore Style:
Serrated both ends
Serration Pitch Diameter:
0.6902 inches both ends
Hardness Rating:
48.0 rockwell c
Mounting Hole Type And Quantity:
3 plain axially through body, first end
Outside Diameter:
4.260 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.114 inches first end
Face Width:
0.380 inches
Hub Style Designator:
Plain first end
Hub Diameter:
2.880 inches first end
Precision Classification:
Quality number 9
Mounting Hole Diameter:
0.380 inches axially through body, first end
Special Features:
Counterbore on 2nd end w/ 2.000 in. Min, 2.001 in. Maximum dia; 0.125 in. Min, 0.140 in. Maximum depth; spur gear teeth 1st end;
chamfered to 0.0600 in. By 45 deg; 32 microinch aa finish on gear teeth, splines, and 2nd end surfaces
Material:
Steel
Style Designator:
Protruding hub

## NSN 3020-00-136-1203

Spur Gear - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A27300