## NSN 3020-00-136-1439

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-136-1439

Outside Diameter:
0.995 inches
Overall Length:
0.344 inches
Bore Diameter:
Between 0.3125 inches and 0.3135 inches
Bore Length:
0.344 inches
Pitch Diameter:
0.943 inches
Securing Hole Quantity:
2
Face Width:
Between 0.055 inches and 0.062 inches
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Hole Location:
Location on hub portion of gear between hub and face, holes 180 degrees apart
Keying Facility:
Not included
Securing Method:
Drilled hole
Lightening Hole:
Not included
Protruding Hub Characteristic:
Stepped
Groove/step Location:
Aa end
Securing Location:
Aa end
Tapered Hole Size:
Nmuber 39
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:

## **NSN 3020-00-136-1439** Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
20
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.1475 inches
Hub End Outside Diameter And Location:
0.687 inches both ends
Distance From Outside Flange/rim To Hub End And Location:
0.282 inches both ends
First Step Face Largest Diameter And Location:
0.755 inches aa end and 0.765 inches bb end
First Step Length And Location:
0.219 inches aa end
Second Step Length And Location:
0.063 inches aa end and 0.073 inches bb end
Material:
Steel, corrosion resisting
Material:
Stainless steel
Surface Treatment:
Passivate
Style Designator:
Plain
Surface Treatment:
Passivated
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-c