NSN 3020-00-137-1865

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-137-1865

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 1.0198 inches and 1.0208 inches
Teeth Quantity:
49
Bore Style:
W/counterbore both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thread Size:
0.060 inches axially through body, first end
Mounting Hole Type And Quantity:
2 threaded axially through body, first end
Outside Diameter:
1.061 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.410 inches first end
Face Width:
0.090 inches
Bore Diameter:
0.313 inches both ends
Counterbore Depth:
0.025 inches second end
Counterbore Diameter:
0.781 inches second end
Hub Style Designator:
1 step first end
End Length:
0.396 inches first end
Precision Classification:
Quality number 10 or quality number 11
End Diameter:
0.448 inches first end
First Step Length:
0.014 inches first end

NSN 3020-00-137-1865

Spur Gear - Page 2 of 2

Fiig: A27300



First Step Diameter:
0.781 inches first end
Special Features:
2nd counterbore on 2nd end w/ 0.3750 in. Dia, 0.0310 in.Min, 0.0340 in. Maximum depth
Material:
Copper alloy
Material Specification:
Qq-c-465 federal specification single material response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No