## NSN 3020-00-137-5356

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-137-5356

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
1.0000 inches
Teeth Quantity:
48
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc axially through body, first end
Mounting Hole Thready Qty Per Inch (tpi):
32 axially through body, first end
Mounting Hole Thread Size:
0.138 inches axially through body, first end
Mounting Hole Type And Quantity:
1 plain axially through body, first end and 1 threaded axially through body, first end
Outside Diameter:
1.042 inches
Nominallength:
0.710 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.585 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.500 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.750 inches first end
Precision Classification:
Quality number 10
Mounting Hole Diameter:
0.070 inches transversely through hub, first end

Special Features:

1 0.070 in. Diameter unthd hole located 90 degrees from thd hole

## NSN 3020-00-137-5356

Spur Gear - Page 2 of 2



Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625, type 1, class 1 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A27300
Mil-std (military Standard):
Mil-a-8625 spec.