NSN 3020-00-137-9697

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-137-9697

Attachment Method:
Clamp and internal ring groove

Pitch Diameter:
Between 2.6656 inches and 2.6666 inches

Teeth Quantity:

1 00
Pitch Diameter:
Between 2.6656 inches and 2.6666 inches
Teeth Quantity:
64
Bore Style:
Plain both ends
Outside Diameter:
2.750 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.368 inches first end
Face Width:
0.162 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.774 inches second end
Clamping Surface Length:
0.140 inches first end
Precision Classification:
Quality number 13
Material:
Aluminum alloy 2024
Surface Treatment:
Oxide film
Surface Treatment Specification:
Mil-c-5541, type 2, grade c, class 2 military specification single treatment response
Style Designator:
Protruding hubs
Shelf Life:
N/a

No

Unit Of Measure:

Demilitarization:

NSN 3020-00-137-9697

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-c-5541 spec.