NSN 3020-00-137-9697

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-137-9697

Attachment Method:
Clamp and internal ring groove

Pitch Diameter:
Between 2.6656 inches and 2.6666 inches

Teeth Quantity:

| 1 00 |
|---|
| Pitch Diameter: |
| Between 2.6656 inches and 2.6666 inches |
| Teeth Quantity: |
| 64 |
| Bore Style: |
| Plain both ends |
| Outside Diameter: |
| 2.750 inches |
| Tooth Form: |
| Standard |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.368 inches first end |
| Face Width: |
| 0.162 inches |
| Bore Diameter: |
| 0.187 inches both ends |
| Hub Style Designator: |
| Split first end |
| Hub Diameter: |
| 0.774 inches second end |
| Clamping Surface Length: |
| 0.140 inches first end |
| Precision Classification: |
| Quality number 13 |
| Material: |
| Aluminum alloy 2024 |
| Surface Treatment: |
| Oxide film |
| Surface Treatment Specification: |
| Mil-c-5541, type 2, grade c, class 2 military specification single treatment response |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |

No

Unit Of Measure:

Demilitarization:

NSN 3020-00-137-9697

Spur Antibacklash Gear - Page 2 of 2



Fiig:

A27300

Mil-std (military Standard):

Mil-c-5541 spec.