NSN 3020-00-139-3179

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-139-3179 **Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: Between 3.9990 inches and 4.0000 inches **Teeth Quantity:** 320 **Bore Style:** Plain both ends **Backlash Designation:** Grade d **Mounting Hole Type And Quantity:** 1 plain axially through body, first end **Outside Diameter:** 0.024 inches **Tooth Form:** Standard Pressure Angle: 20.0000 degrees Face Width: 0.125 inches **Bore Diameter:** 2.812 inches both ends **Precision Classification:** Quality number 11 **Mounting Hole Diameter:** 0.093 inches axially through body, first end **Bolt Hole Circle Diameter:** 3.300 inches axially through body, first end Material: Aluminum alloy 6061 **Material Specification:** Qq-a-250/11, t6 federal specification single material response **Surface Treatment:** Chromate **Surface Treatment Specification:** Mil-c-5541 military specification single treatment response **Style Designator:** Hubless

Shelf Life:

N/a

NSN 3020-00-139-3179

Spur Gear - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-5541 spec.