NSN 3020-00-139-3723



Sprocket Wheel - Page 1 of 3 View Online at https://aerobasegroup.com/nsn/3020-00-139-3723 **Outside Diameter:** 3.980 inches **Overall Length:** 1.500 inches **Keyway Width:** 0.250 inches **Thread Size:** 3/8-16 **Bore Diameter:** 1.625 inches Bore Length: 1.500 inches **Distance From Center Of Bore To Bottom Of Keyway:** 0.9375 inches Pitch Diameter: 3.610 inches **Securing Hole Quantity: Furnished Items And Quantity:** Setscrew 1 Face Width: 0.459 inches Design Form: Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** 90 degrees from keyway **Keying Facility:** Included **Keying Facility Type:** Keyway **Securing Method:** Threaded hole **Lightening Hole:** Not included **Protruding Hub Characteristic:**

Grooved **Groove/step Location:**

Aa end

NSN 3020-00-139-3723 Sprocket Wheel - Page 2 of 3



Securing Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
1
Teeth Quantity Per Row:
15
Asa Standard Chain Number:
60
Hardness Rating Test Method:
Not rated
Bore Bearing:
Not included
Hub External Keyway:
Not included
Tooth Pitch:
0.750 inches
First End Groove Diameter And Location:
2.823 inches aa end
First End Groove Width And Location:
0.246 inches aa end
First End Length From Groove To End And Location:
0.812 inches aa end
Hub End Outside Diameter And Location:
3.062 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
1.041 inches aa end
Material:
Steel
Material:
Steel
Quantity:
1
Surface Treatment:
Oxide
Style Designator:
Plain
Surface Treatment:
Black oxide
Shelf Life:

N/a

NSN 3020-00-139-3723

Sprocket Wheel - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

Т353-с