# NSN 3020-00-139-4137

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-139-4137

## **Body Style:**

Plain, solid

## **Pitch Diameter:**

Between 0.4326 inches and 0.4333 inches

# Teeth Quantity:

52

# Bore Style:

Plain both ends

## **Backlash Designation:**

Grade c

## **Outside Diameter:**

0.449 inches

#### Tooth Form:

Standard

### Pressure Angle:

20.0000 degrees

## Distance Between Body Face And Protruding Hub End:

0.125 inches first end

#### Face Width:

0.125 inches

# Bore Diameter:

0.156 inches both ends

# Hub Style Designator:

Pinned first end

## Hub Diameter:

0.310 inches first end

## **Precision Classification:**

Quality number 12

## Material:

Steel comp 303

## **Material Specification:**

Qq-s-764, type 303, cond a federal specification single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Mil-f-14072, finish e300 military specification single treatment response

# Style Designator:

Protruding hub

### Shelf Life:

N/a

#### Unit Of Measure:

--

# NSN 3020-00-139-4137

Spur Gear - Page 2 of 2

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-f-14072 spec.

