NSN 3020-00-139-4538

Spur Gear - Page 1 of 2

response



View Online at https://aerobasegroup.com/nsn/3020-00-139-4538

| Body Style: |
|---|
| Plain, solid |
| Attachment Method: |
| Mounting hole |
| Pitch Diameter: |
| 1.6667 inches |
| Teeth Quantity: |
| 120 |
| Bore Style: |
| Plain both ends |
| Mounting Hole Type And Quantity: |
| 4 plain axially through body, first end |
| Outside Diameter: |
| 1.699 inches |
| Pressure Angle: |
| 20.0000 degrees |
| Distance Between Body Face And Protruding Hub End: |
| 0.623 inches first end |
| Face Width: |
| 0.126 inches |
| Bore Diameter: |
| 0.250 inches both ends |
| Hub Style Designator: |
| 2 steps first end |
| End Length: |
| 0.125 inches second end |
| End Diameter: |
| 0.187 inches second end |
| First Step Length: |
| 0.375 inches first end |
| First Step Diameter: |
| 0.210 inches second end |
| Second Step Length: |
| 0.123 inches first end |
| Second Step Diameter: |
| 0.310 inches first end |
| Mounting Hole Diameter: |
| 0.375 inches axially through body, first end |
| Material: |
| Steel comp 303 or steel comp 303se |
| Material Specification: |
| Qq-s-764, type 303-canceled federal specification 1st material response or qq-s-764, type 303se-canceled federal specification 2nd material |

NSN 3020-00-139-4538

Spur Gear - Page 2 of 2

Mil-std (military Standard):

Mil-f-14072 spec.



| Surface Treatment: |
|---|
| Passivate |
| Surface Treatment Specification: |
| Mil-f-14072, finish e300 military specification single treatment response |
| Style Designator: |
| Protruding hubs |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A27300 |