NSN 3020-00-139-5963

Gear Cluster - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/3020-00-139-5963

Bore Style:
Plain both ends
Design Type:
Spur second gear
Construction:
Solid
Outside Diameter:
0.353 inches first gear
Nominallength:
0.500 inches
Hub Length:
0.188 inches first end
Bore Diameter:
0.125 inches both ends
Hub Style Designator:
Plain between first and second gear
Hub Diameter:
nub Diameter.
0.250 inches first end
0.250 inches first end
0.250 inches first end Material:
0.250 inches first end Material: Aluminum alloy 6061
0.250 inches first end Material: Aluminum alloy 6061 Material Specification:
0.250 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response
0.250 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment:
0.250 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment: Anodize
0.250 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment: Anodize Shelf Life:
0.250 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment: Anodize Shelf Life: N/a
0.250 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment: Anodize Shelf Life: N/a
0.250 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment: Anodize Shelf Life: N/a Unit Of Measure:
0.250 inches first end Material: Aluminum alloy 6061 Material Specification: Qq-a-225/8, t6 federal specification single material response Surface Treatment: Anodize Shelf Life: N/a Unit Of Measure: Demilitarization: