NSN 3020-00-140-3628

Spur Gear - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/3020-00-140-3628

Plain, solid
Pitch Diameter:
Between 0.9576 inches and 0.9583 inches
Teeth Quantity:
69
Bore Style:
Plain both ends
Backlash Designation:
Grade d
Outside Diameter:
0.985 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.250 inches first end
Face Width:
0.130 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Pinned first end
Hub Diameter:
0.380 inches first end
Precision Classification:
Quality number 12
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6, t4 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:

--

NSN 3020-00-140-3628

Spur Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.