NSN 3020-00-141-2147

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-141-2147

Outside Diameter:
13.306 inches
Overall Length:
4.000 inches
Keyway Width:
Between 0.621 inches and 0.623 inches
Bore Diameter:
Between 2.437 inches and 2.438 inches
Bore Length:
4.000 inches
Distance From Center Of Bore To Bottom Of Keyway:
Between 1.517 inches and 1.524 inches and 1.475 inches and 1.482 inches
Pitch Diameter:
12.746 inches
Face Width:
1.704 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Counterbore Feature:
Not included
Keying Facility:
Included
Keying Facility Type:
Tapered keyway
Lightening Hole:
Not included
Keying Facility Largest Dimension Location:
Aa end
Protruding Hub Characteristic:
Stepped
Groove/step Location:
Aa end
Belt/chain/film Size For Which Designed:
Roller chain
Roller Chain Pitch Type For Which Designed:
Single pitch
Teeth Row Quantity:
2

NSN 3020-00-141-2147

Sprocket Wheel - Page 2 of 2



Center To Center Distance Between Teeth Rows:

1.147 inches

Teeth Quantity Per Row:

40

Asa Standard Chain Number:

80-2

Hardness Rating Test Method:

Not rated

Bore Bearing:

Not included

Hub External Keyway:

Not included

Tooth Pitch:

1.000 inches

First Step Face Largest Diameter And Location:

11.746 inches aa end

First Step Length And Location:

2.000 inches aa end

Hub End Outside Diameter And Location:

4.000 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

2.148 inches aa end

Material:

Steel, qq-s-633, comp c1020-canceled

Material:

Steel comp 1020

Material Specification:

Qq-s-633, comp c1020-canceled federal specification single material response

Quantity:

1

Style Designator:

Plain

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

Т353-с