

NSN 3020-00-141-3729 Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-141-3729 **Body Style:** Plain, solid **Attachment Method:**

Mounting hole Pitch Diameter: 0.4167 inches **Teeth Quantity:** 30 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 56 transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 0.443 inches Nominallength: 0.221 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.128 inches first end **Face Width:**

0.093 inches

Bore Diameter:

0.125 inches both ends

Hub Style Designator:

Pinned first end

Hub Diameter:

0.250 inches first end

Precision Classification:

Quality number 10 or quality number 11

Material:

Steel comp 303

Material Specification:

Qq-s-764, type 303, cond a federal specification single material response

NSN 3020-00-141-3729

Spur Gear - Page 2 of 2



_	•		_	-		
ن	ırfa	\sim	I rc	nter	nor	٠.

Passivate

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300