NSN 3020-00-141-6108

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-141-6108

Attachment Method:
Clamp
Pitch Diameter:
Between 1.4993 inches and 1.5000 inches
Teeth Quantity:
120
Bore Style:
Plain both ends
Backlash Designation:
Grade d
Outside Diameter:
1.524 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.281 inches first end
Face Width:
0.104 inches
Bore Diameter:
1.525 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.186 inches first end
Clamping Surface Length:
0.250 inches first end
Precision Classification:
Quality number 12
Material:
Stainless steel spring
Material Specification:
Qq-s-764 federal specification single material response hub
Surface Treatment:
Passivate hub
Surface Treatment Specification:
Qq-p-35, type 2 federal specification single treatment response hub
Style Designator:
Protruding hub
Shelf Life:
N/a

NSN 3020-00-141-6108

Spur Antibacklash Gear - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A27300