NSN 3020-00-141-6127

Spur Gear-slip Clutch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-141-6127 **Attachment Method:** Mounting hole Pitch Diameter: 1.5000 inches **Torque Capacity:** Between 1.00 inch-ounces and 10.11 inch-ounces **Teeth Quantity:** 120 **Bore Style:** Plain both ends **Mounting Hole Thread Series Designator:** Unc transversely through hub, first end **Mounting Hole Thread Size:** 0.086 inches transversely through hub, first end **Mounting Hole Type And Quantity:** 1 threaded transversely through hub, first end **Outside Diameter:** 1.5160 inches Nominallength: 0.562 inches **Tooth Form:** Special **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.225 inches first end **Face Width:** 0.125 inches **Bore Diameter:** 0.188 inches both ends Distance Between Face Edge And Body End: 0.212 inches **Hub Style Designator:** Pinned first end **Hub Diameter:** 0.500 inches first end Material: Steel **Material Specification:** Qq-s-764 type 303 cond a federal specification single material response

Surface Treatment:

Passivate

NSN 3020-00-141-6127

Spur Gear-slip Clutch - Page 2 of 2



Sty	le [)es	ign	ato	r:

Adjustable torque, spring washer loaded

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300