## NSN 3020-00-141-8310

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-141-8310 **Outside Diameter:** 0.938 inches **Overall Length:** 0.313 inches **Bolt Circle Diameter:** 0.437 inches **Thread Size:** No. 6-32 **Bore Diameter:** 0.250 inches Bore Length: 0.313 inches **Drilled Hole Diameter:** 0.062 inches Pitch Diameter: 0.830 inches **Securing Hole Quantity: Furnished Items And Quantity:** 2 pins Face Width: 0.109 inches Design Form: Plain **Bore Type:** Straight **Counterbore Feature:** Not included **Hole Location:** Drilled holes 180 degrees apart **Keying Facility:** Not included **Securing Method:** Drilled hole **Lightening Hole:** Not included **Protruding Hub Characteristic:** Plain Belt/chain/film Size For Which Designed: Ladder chain **Teeth Row Quantity:** 

## **NSN 3020-00-141-8310** Sprocket Wheel - Page 2 of 2



| Teeth Quantity Per Row:                                   |
|---|
| 14  |
| Hardness Rating Test Method:                              |
| Not rated   |
| Bore Bearing:   |
| Not included  |
| Hub External Keyway:                                      |
| Not included  |
| Tooth Pitch:  |
| 0.185 inches  |
| Hub End Outside Diameter And Location:                    |
| 0.625 inches both ends                                    |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.203 inches both ends                                    |
| Special Features:   |
| 1 threaded and 2 drilled securing holes                   |
| Material:   |
| Steel   |
| Material:   |
| Steel   |
| Surface Treatment:  |
| Cadmium and chromate                                      |
| Style Designator:   |
| Plain   |
| Surface Treatment:  |
| Cadmium plated and chromate, qq-p-416, type 2, class c    |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| T353-c  |
|   |