

View Online at <https://aerobasegroup.com/nsn/3020-00-141-8884>

Groove Depth:

0.688 inches

Groove Width:

Between 0.656 inches and 0.658 inches

Outside Diameter:

5.920 inches

Keyway Width:

Between 0.249 inches and 0.250 inches

Bore Length:

2.313 inches

Distance From Center Of Bore To Bottom Of Keyway:

Between 0.707 inches and 0.719 inches

V Groove Angle In Deg:

38.0

Pitch Diameter:

5.420 inches

Furnished Items And Quantity:

N/a

Taper Bore Major Diameter:

Between 1.250 inches and 1.251 inches

Taper Bore Minor Diameter:

Between 1.225 inches and 1.226 inches

Material And Location:

Steel, mil-s-20166, type b, grade m

Face Width:

2.500 inches

Design Form:

Webbed

Bore Type:

Tapered

Bearings:

Not included

Taper Major Diameter Location:

Aa end

Groove Quantity:

3

Counterbore Feature:

Not included

Keying Facility:

Included

Keying Facility Type:

Keyway

Split Hub Feature:

Not included

Web/spoke Relationship To Face Centerline:

Not offset

Lightening Hole:

Included

Integral Cooling Vane:

Not included

Groove Shape:

V

Standard V-belt Section Designation For Which Designed:

B

Bore Feature:

Included

Keying Facility Largest Dimension Location:

Aa end

Hub End Outside Diameter And Location:

2.125 inches both ends

Distance From Outside Flange/rim To Hub End And Location:

0.188 inches both ends

Quantity:

1

Surface Treatment:

Zinc

Style Designator:

Webbed or spoked

Surface Treatment:

Zinc plated

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T353-a