

View Online at <https://aerobasegroup.com/nsn/3020-00-151-7587>

Outside Diameter:

3.000 inches

Overall Length:

0.670 inches

Bore Diameter:

0.627 inches

Bore Length:

0.670 inches

Drilled Hole Diameter:

Between 0.189 inches and 0.192 inches

Securing Hole Quantity:

2

Face Width:

0.135 inches

Design Form:

Plain

Bore Type:

Straight

Metallic Hardness Rating And Location:

33.0 rockwell c hub and 38.0 rockwell c hub

Counterbore Feature:

Not included

Hole Location:

Aa portion of hub

Keying Facility:

Not included

Securing Method:

Drilled hole

Lightening Hole:

Not included

Protruding Hub Characteristic:

Plain

Teeth Row Quantity:

1

Teeth Quantity Per Row:

5

Hardness Rating Test Method:

Rockwell

Teeth Hardness Rating:

Between 30.0 rockwell c and 35.0 rockwell c

Bore Bearing:

Not included

Hub External Keyway:

Not included

Hub End Outside Diameter And Location:

1.125 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.530 inches aa end

Special Features:

Item name, sprocket rear unload

Material:

Steel, mil-s-6758 and steel, mil-s-18729, comp 4130, cond n

Material:

Steel comp 4130 and steel comp 4130

Material Specification:

Mil-s-6758 military specification 1st material response and mil-s-18729, comp 4130, cond n military specification 2nd material response

Surface Treatment:

Phosphate

Style Designator:

Plain

Surface Treatment:

Phosphate

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T353-c

Mil-std (military Standard):

Mil-s-6758 spec.