

View Online at <https://aerobasegroup.com/nsn/3020-00-151-7587>

**Outside Diameter:**

3.000 inches

**Overall Length:**

0.670 inches

**Bore Diameter:**

0.627 inches

**Bore Length:**

0.670 inches

**Drilled Hole Diameter:**

Between 0.189 inches and 0.192 inches

**Securing Hole Quantity:**

2

**Face Width:**

0.135 inches

**Design Form:**

Plain

**Bore Type:**

Straight

**Metallic Hardness Rating And Location:**

33.0 rockwell c hub and 38.0 rockwell c hub

**Counterbore Feature:**

Not included

**Hole Location:**

Aa portion of hub

**Keying Facility:**

Not included

**Securing Method:**

Drilled hole

**Lightening Hole:**

Not included

**Protruding Hub Characteristic:**

Plain

**Teeth Row Quantity:**

1

**Teeth Quantity Per Row:**

5

**Hardness Rating Test Method:**

Rockwell

**Teeth Hardness Rating:**

Between 30.0 rockwell c and 35.0 rockwell c

**Bore Bearing:**

Not included

**Hub External Keyway:**

Not included

**Hub End Outside Diameter And Location:**

1.125 inches aa end

**Distance From Outside Flange/rim To Hub End And Location:**

0.530 inches aa end

**Special Features:**

Item name, sprocket rear unload

**Material:**

Steel, mil-s-6758 and steel, mil-s-18729, comp 4130, cond n

**Material:**

Steel comp 4130 and steel comp 4130

**Material Specification:**

Mil-s-6758 military specification 1st material response and mil-s-18729, comp 4130, cond n military specification 2nd material response

**Surface Treatment:**

Phosphate

**Style Designator:**

Plain

**Surface Treatment:**

Phosphate

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T353-c

**Mil-std (military Standard):**

Mil-s-6758 spec.