NSN 3020-00-151-7588



Sprocket Wheel - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-151-7588 **Outside Diameter:** 3.000 inches **Overall Length:** 0.625 inches **Bore Diameter:** 0.688 inches **Bore Length:** 0.670 inches **Drilled Hole Diameter:** 0.189 inches **Securing Hole Quantity:** Face Width: 0.135 inches **Design Form:** Plain **Bore Type:** Straight **Metallic Hardness Rating And Location:** 33.0 rockwell c body and 38.0 rockwell c body **Counterbore Feature:** Not included **Hole Location:** On hub **Keying Facility:** Not included **Securing Method:** Drilled hole **Lightening Hole:** Not included **Protruding Hub Characteristic: Teeth Row Quantity: Teeth Quantity Per Row:**

Hardness Rating Test Method: Rockwell **Bore Bearing:** Not included

Hub External Keyway:

Not included

NSN 3020-00-151-7588

Sprocket Wheel - Page 2 of 2



| Hub End C | Outside | Diameter | And | Location: |
|-----------|---------|----------|-----|-----------|
|-----------|---------|----------|-----|-----------|

1.125 inches aa end

Distance From Outside Flange/rim To Hub End And Location:

0.530 inches aa end

Material:

Steel, mil-s-18729, comp 4130, cond n and steel, mil-s-6758

Material:

Steel comp 4130 and steel comp 4130

Material Specification:

Mil-s-18729, comp 4130, cond n military specification 1st material response and mil-s-6758 military specification 2nd material response

Surface Treatment:

Phosphate

Style Designator:

Plain

Surface Treatment:

Phosphate

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

T353-c

Mil-std (military Standard):

Mil-s-18729 spec.