NSN 3020-00-152-9827

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-152-9827

Attack mont Mathad
Attachment Method:
Mounting hole
Teeth Quantity:
264
Bore Style:
W/counterbore both ends
Pitch Radius:
3.5000 inches
Mounting Hole Type And Quantity:
4 counterbored transversely through hub, second end and 4 plain transversely through hub, second end
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.0650 inches first end
Face Width:
0.625 inches
Bore Diameter:
2.378 inches counterbore, first end
Counterbore Depth:
0.270 inches counterbore, first end
Counterbore Diameter:
3.844 inches counterbore, first end
Hub Style Designator:
Plain first end
Hub Diameter:
4.5800 inches first end
Outside Radius:
3.8750 inches
Arc Length:
2.8750 inches
Mounting Hole Diameter:
0.196 inches transversely through hub, second end and 0.188 inches transversely through hub, second end
Bolt Hole Circle Diameter:
4.225 inches transversely through hub, second end
Material:
Copper alloy
Material Specification:
Mil-c-20159 type 1 copper-nickel military specification single material response
Surface Treatment:
Oxide

NSN 3020-00-152-9827

Spur Gear Sector - Page 2 of 2



Mil-f-495 black oxide military specification single treatment response

Style Designator:

Protruding hub

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-20159 spec.