NSN 3020-00-152-9828

Spur Gear Sector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-152-9828

Attachment Method:
Mounting hole
Bore Style:
W/counterbore counterbore, first end
Mounting Hole Type And Quantity:
4 counterbored axially through hub, first end and 4 plain axially through hub, first end
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.350 inches first end
Face Width:
0.625 inches
Bore Diameter:
2.378 inches both ends
Counterbore Depth:
0.450 inches counterbore, first end
Counterbore Diameter:
3.844 inches counterbore, first end
Hub Style Designator:
Plain first end
Hub Diameter:
4.580 inches first end
Mounting Hole Diameter:
0.196 inches axially through hub, first end and 0.188 inches axially through hub, first end
Bolt Hole Circle Diameter:
4.225 inches axially through hub, first end
Special Features:
Counterbore dia: 3.844 in. Nom and 2.750 in. Nom
Material:
Copper alloy 964
Material Specification:
Mil-c-20159, type 1 military specification single material response
Surface Treatment:
Oxide
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:

--

NSN 3020-00-152-9828

Spur Gear Sector - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-c-20159 spec.