## NSN 3020-00-153-0288

Spur Gear - Page 1 of 2





## Body Style:

Webbed, solid

#### **Attachment Method:**

Mounting hole

## Pitch Diameter:

Between 1.2490 inches and 1.2500 inches

## **Teeth Quantity:**

60

Bore Style:

Plain both ends

Hardness Rating:

44.0 rockwell c and 48.0 rockwell c

#### Mounting Hole Type And Quantity:

4 plain axially through body, first end

#### Outside Diameter:

#### 1.291 inches

Tooth Form:

Standard

#### Pressure Angle:

20.0000 degrees

#### Body Recess Depth:

0.062 inches second end

## Face Width:

0.250 inches

#### Bore Diameter:

0.438 inches both ends

#### **Precision Classification:**

Quality number 10 or quality number 11

#### Mounting Hole Diameter:

0.120 inches axially through body, first end

#### Material:

Steel comp 6150

#### **Material Specification:**

Mil-s-8503 military specification single material response

#### Surface Treatment:

Cadmium

## Surface Treatment Specification:

Fs10052, cage 72314 assn standard single treatment response

#### Style Designator:

Hubless, recessed body

#### Shelf Life:

N/a

# NSN 3020-00-153-0288

Spur Gear - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-s-8503 spec.

