## NSN 3020-00-153-3133

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-153-3133

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 0.6937 inches and 0.6944 inches
Teeth Quantity:
50
Bore Style:
Plain both ends
Mounting Hole Thread Series Designator:
Unc transversely through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 transversely through hub, first end
Mounting Hole Thread Size:
0.112 inches transversely through hub, first end
Mounting Hole Type And Quantity:
1 threaded transversely through hub, first end
Outside Diameter:
0.721 inches
Nominallength:
0.320 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.195 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
1 step first end
End Length:
0.020 inches first end
Precision Classification:
Quality number 12
End Diameter:
0.250 inches first end
First Step Length:
0.175 inches first end

## NSN 3020-00-153-3133

Spur Gear - Page 2 of 2

A27300



First Step Diameter:
0.375 inches first end
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiio: