## NSN 3020-00-155-2976

Spur Gear - Page 1 of 2



Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
3.3750 inches
Teeth Quantity:
27
Bore Style:
Plain both ends
Hardness Rating:
55.0 rockwell c and 60.0 rockwell c
Mounting Hole Type And Quantity:
2 plain axially through body, first end
Outside Diameter:
3.623 inches
Nominallength:
1.875 inches
Tooth Form:
Standard
Pressure Angle:
25.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.879 inches first end
Face Width:
0.495 inches
Bore Diameter:
2.029 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
2.498 inches second end
Clamping Surface Length:
0.250 inches first end
Mounting Hole Diameter:
0.125 inches axially through body, first end
Bolt Hole Circle Diameter:
2.750 inches axially through body, first end
Material:
Steel comp 8620
Material Specification:

66, aisi/sae 8620 federal standard single material response

## NSN 3020-00-155-2976

Spur Gear - Page 2 of 2



Sty	ما	n	20	in	n	at.	۸r	
Oty:	Œ	$\boldsymbol{\mathcal{L}}$	C3	ıy	••	aι	vı	•

Protruding hubs

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A27300