NSN 3020-00-157-9599

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-157-9599

Body Style:
Plain, solid
Attachment Method:
Clamp
Pitch Diameter:
Between 0.8326 inches and 0.8333 inches
Teeth Quantity:
40
Bore Style:
Plain both ends
Backlash Designation:
Grade d
Outside Diameter:
0.875 inches
Tooth Form:
Standard
Pressure Angle:
20.0000 degrees
Distance Between Body Face And Protruding Hub End:
0.281 inches first end
Face Width:
0.125 inches
Bore Diameter:
0.187 inches both ends
Hub Style Designator:
Split first end
Hub Diameter:
0.312 inches first end
Clamping Surface Length:
0.250 inches first end
Precision Classification:
Quality number 12
Material:
Steel comp 303
Material Specification:
Qq-s-764, type 303, cond a federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type 2 federal specification single treatment response
Style Designator:

Protruding hub

NSN 3020-00-157-9599

Spur Gear - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A27300