## NSN 3020-00-158-0167

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-158-0167

Body Style:
Plain, solid
Attachment Method:
Mounting hole
Pitch Diameter:
Between 2.8115 inches and 2.8120 inches
Teeth Quantity:
135
Bore Style:
Tapered w/keyway first end
Mounting Hole Thread Series Designator:
Unc axially through hub, first end
Mounting Hole Thready Qty Per Inch (tpi):
40 axially through hub, first end
Mounting Hole Thread Size:
0.112 inches axially through hub, first end
Mounting Hole Type And Quantity:
3 threaded axially through hub, first end
Outside Diameter:
2.852 inches
Tooth Form:
Standard
Pressure Angle:
14.5000 degrees
Distance Between Body Face And Protruding Hub End:
0.219 inches first end
Face Width:
0.125 inches
Keyway Width:
0.063 inches first end
Distance From Bore Center To Keyway Bottom:
0.133 inches first end
Taper Major Diameter:
0.182 inches first end
Counterbore Depth:
0.125 inches second end
Counterbore Diameter:
1.375 inches second end
Hub Style Designator:
1 step first end
End Length:
0.094 inches first end

## NSN 3020-00-158-0167

Spur Gear - Page 2 of 2



**End Diameter:** 

0.500 inches first end

First Step Length:

0.125 inches first end

First Step Diameter:

1.625 inches first end

Material:

Stainless steel

Style Designator:

Protruding hub

Shelf Life:

-----

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A27300