## NSN 3020-00-162-7324

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-162-7324

**Body Style:** Plain, solid **Attachment Method:** Mounting hole Pitch Diameter: 4.8333 inches **Teeth Quantity:** 29 **Mounting Hole Thread Series Designator:** Unc axially through hub, first end Mounting Hole Thready Qty Per Inch (tpi): 18 axially through hub, first end **Hardness Rating:** 58.0 rockwell c and 62.0 rockwell c **Mounting Hole Thread Size:** 0.313 inches axially through hub, first end **Mounting Hole Type And Quantity:** 4 threaded axially through hub, first end **Outside Diameter:** 5.161 inches **Tooth Form:** Standard **Pressure Angle:** 25.0000 degrees **Distance Between Body Face And Protruding Hub End:** 1.500 inches both ends **Face Width:** 1.250 inches **Hub Style Designator:** 2 steps first end **Hub Diameter:** 1.772 inches both ends **End Length:** 0.880 inches both ends **End Diameter:** 0.772 inches both ends First Step Length:

0.500 inches both ends First Step Diameter: 2.250 inches both ends **Second Step Length:** 0.120 inches both ends

## NSN 3020-00-162-7324

Spur Gear - Page 2 of 2

No Fiig: A27300



Second Step Diameter:
3.000 inches both ends
<b>Bolt Hole Circle Diameter:</b>
1.120 inches axially through hub, first end
Special Features:
Two mtg holes on each end of hub 180 degrees apart
Material:
Steel comp 8620
Material Specification:
66, aisi/sae federal standard single material response
Style Designator:
Protruding hubs
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: