## NSN 3020-00-163-0466

Spur Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-163-0466

Body Style:	
Plain, solid	
Attachment Method:	
Mounting hole	
End Application:	
2350-01-115-1579	
Pitch Diameter:	
2.8000 inches	
Teeth Quantity:	
28	
Bore Style:	
W/counterbore both ends	
Backlash Designation:	
Grade a	
Mounting Hole Thread Series Designator:	
Unc axially through body, first end	
Mounting Hole Thready Qty Per Inch (tpi):	
28 axially through body, first end	
Hardness Rating:	
33.0 rockwell c and 38.0 rockwell c	
Mounting Hole Thread Size:	
0.250 inches axially through body, first end	
Mounting Hole Type And Quantity:	
4 threaded axially through body, first end	
Outside Diameter:	
2.998 inches	
Tooth Form:	
Standard	
Pressure Angle:	
20.0000 degrees	
Face Width:	
0.688 inches	
Bore Diameter:	
1.370 inches both ends	
Counterbore Depth:	
0.481 inches first end	
Counterbore Diameter:	
1.575 inches first end	
Bolt Hole Circle Diameter:	
2.000 inches axially through body, first end	
Special Features:	

Special Features

Bore grooved 1.580 in. Dia, 0.090 in.Wide at bottom of counterbore, 125 microinch finish both ends, 63 microinch finish on tooth faces, mounting holes counter sunk 90 degreesporm 10 degrees to 0.260 in.Min, 0.280 in.Max both ends

## NSN 3020-00-163-0466

Spur Gear - Page 2 of 2

**Fiig:** A27300



Material:
Steel comp 4140
Material Specification:
66, aisi/sae federal standard single material response
Style Designator:
Hubless
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No