

View Online at <https://aerobasegroup.com/nsn/3020-00-163-5304>

Bore Style:

W/counterbore first end

Design Type:

Spur second gear

Construction:

Solid

Hardness Rating:

54.0 rockwell c and 56.0 rockwell c

Outside Diameter:

3.697 inches first gear

Nominallength:

1.310 inches

Hub Length:

0.270 inches between first and second gear

Bore Diameter:

0.620 inches first end

Counterbore Depth:

0.245 inches first end

Counterbore Diameter:

1.750 inches first end

Hub Style Designator:

Plain between first and second gear

Hub Diameter:

0.810 inches between first and second gear

Precision Classification:

Quality number 10 all gears or quality number 11 all gears

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Mil-c-8837, type 2, class 2 military specification single treatment response

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A270a0

Mil-std (military Standard):

Mil-c-8837 spec.