## NSN 3020-00-163-5319

Spur Antibacklash Gear - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-163-5319 **Attachment Method:** Clamp Pitch Diameter: 1.2750 inches **Teeth Quantity:** 102 **Bore Style:** Plain both ends **Outside Diameter:** 1.299 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees **Distance Between Body Face And Protruding Hub End:** 0.145 inches first end **Face Width:** 0.064 inches **Bore Diameter:** 0.125 inches both ends **Hub Style Designator:** Split first end **Hub Diameter:** 0.188 inches first end **Clamping Surface Length:** 0.107 inches first end **Precision Classification:** Quality number 9 Material: Aluminum alloy 2024 **Material Specification:** Qq-a-225/4, t4 federal specification single material response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 1 military specification single treatment response Style Designator: Protruding hub Shelf Life:

N/a **Unit Of Measure:** 

## NSN 3020-00-163-5319

Spur Antibacklash Gear - Page 2 of 2



Demilitarization:

No

Fiig:

A27300

Mil-std (military Standard):

Mil-a-8625 spec.