## NSN 3020-00-165-4250

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-165-4250

Counterbore Diameter:
0.188 inches
Counterbore Depth:
0.160 inches
Outside Diameter:
0.317 inches
Overall Length:
0.250 inches
Bore Diameter:
0.094 inches
Bore Length:
0.250 inches
Drilled Hole Diameter:
Between 0.047 inches and 0.049 inches
Securing Hole Quantity:
1
Face Width:
0.125 inches
Guide:
Not included
Design Form:
Plain
Bore Type:
Straight
Metallic Hardness Rating And Location:
58.0 rockwell c body and 60.0 rockwell c body
Counterbore Feature:
Included
Counterbore Location:
Aa end
Hole Location:
Thru hub
Keying Facility:
Not included
Securing Method:
Drilled hole
Lightening Hole:
Not included
Belt/chain/film Size For Which Designed:
Positive drive belt
Teeth Row Quantity:

## **NSN 3020-00-165-4250** Sprocket Wheel - Page 2 of 2



Teeth Quantity Per Row:
39
Hardness Rating Test Method:
Rockwell
Teeth Hardness Rating:
Between 58.0 rockwell c and 60.0 rockwell c
Bore Bearing:
Not included
Tooth Pitch:
0.128 inches
Hub End Outside Diameter And Location:
0.250 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.125 inches aa end
Material:
Steel, qq-s-763, class 440c, cond a
Material:
Steel comp 440c
Material Specification:
Qq-s-763, class 440c, cond a federal specification single material response
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-с