
NSN 3020-00-166-0271

Sprocket Wheel - Page 1 of 2





Outside Diameter: 2.050 inches **Overall Length:** 0.620 inches **Bore Diameter:** Between 0.990 inches and 0.991 inches **Bore Length:** 0.620 inches **Drilled Hole Diameter:** Between 0.187 inches and 0.192 inches Pitch Diameter: 1.915 inches Securing Hole Quantity: 1 Face Width: 0.110 inches **Design Form:** Plain Bore Type: Straight **Counterbore Feature:** Not included Hole Location: On hub end **Keying Facility:** Not included **Securing Method:** Drilled hole **Lightening Hole:** Not included **Protruding Hub Characteristic:** Plain Securing Location: Aa end Belt/chain/film Size For Which Designed: Roller chain **Roller Chain Pitch Type For Which Designed:** Single pitch **Teeth Row Quantity:** 1 Teeth Quantity Per Row: 24

NSN 3020-00-166-0271 Sprocket Wheel - Page 2 of 2



| Asa Standard Chain Number: |
|---|
| 25 |
| Bore Bearing: |
| Not included |
| Tooth Pitch: |
| 0.250 inches |
| Hub End Outside Diameter And Location: |
| 1.500 inches aa end |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.510 inches aa end |
| Surface Treatment: |
| Oxide |
| Style Designator: |
| Plain |
| Surface Treatment: |
| Black oxide mil-c-13924 class 1 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| Т353-с |