## NSN 3020-00-166-2023

Flat Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-166-2023

#### **Outside Diameter:**

2.000 inches

#### **Overall Length:**

0.906 inches

#### Outside Diameter:

2.011 inches

#### Thread Size:

2-56

#### Bore Diameter:

Between 0.380 inches and 0.385 inches

Bore Length:

#### 0.906 inches

Flange Width:

#### 0.031 inches

#### Flange Quantity:

1

### Securing Hole Quantity:

2

#### Material And Location:

Aluminum

#### Face Width:

0.474 inches

#### **Design Form:**

Plain

#### Bore Type:

Straight

#### Bearings:

Not included

#### Counterbore Feature:

Not included

#### Hole Location:

Longitudinally through hub, 0.562 in. C to c apart

#### **Keying Facility:**

Not included

#### Securing Method:

Threaded hole

#### Split Hub Feature:

Not included

#### Lightening Hole:

Not included

#### Integral Cooling Vane:

Not included

# **NSN 3020-00-166-2023** Flat Pulley - Page 2 of 2

Crown Face:
Not included
Rim Type:
Solid
Flange Location:
Outside
Bore Feature:
Included
Protruding Hub Characteristic:
Stepped
Securing Location:
Aa end
Hub End Outside Diameter And Location:
0.750 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.432 inches aa end
First Step Face Largest Diameter And Location:
1.000 inches aa end
First Step Length And Location:
0.342 inches aa end
Second Step Length And Location:
0.090 inches aa end
Hub End Outside Diameter And Location:
0.750 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.432 inches aa end
Special Features:
Two 0.126 in. Wide by 0.185 in. Lg slots 180 degrees apart on hub
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Т353-а

