NSN 3020-00-166-2023

Flat Pulley - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-166-2023 **Outside Diameter:** 2.000 inches **Overall Length:** 0.906 inches **Outside Diameter:** 2.011 inches **Thread Size:** 2-56 **Bore Diameter:** Between 0.380 inches and 0.385 inches **Bore Length:** 0.906 inches Flange Width: 0.031 inches Flange Quantity: **Securing Hole Quantity:** 2 **Material And Location:** Aluminum Face Width: 0.474 inches **Design Form:** Plain **Bore Type:** Straight Bearings: Not included **Counterbore Feature:** Not included **Hole Location:** Longitudinally through hub, 0.562 in. C to c apart **Keying Facility:** Not included **Securing Method:** Threaded hole **Split Hub Feature:** Not included **Lightening Hole:**

Not included

Not included

Integral Cooling Vane:

NSN 3020-00-166-2023 Flat Pulley - Page 2 of 2



Crown Face:
Not included
Rim Type:
Solid
Flange Location:
Outside
Bore Feature:
Included
Protruding Hub Characteristic:
Stepped
Securing Location:
Aa end
Hub End Outside Diameter And Location:
0.750 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.432 inches aa end
First Step Face Largest Diameter And Location:
1.000 inches aa end
First Step Length And Location:
0.342 inches aa end
Second Step Length And Location:
0.090 inches aa end
Hub End Outside Diameter And Location:
0.750 inches aa end
Distance From Outside Flange/rim To Hub End And Location:
0.432 inches aa end
Special Features:
Two 0.126 in. Wide by 0.185 in. Lg slots 180 degrees apart on hub
Style Designator:
Plain
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T353-a