## NSN 3020-00-167-4208



Spur Gear - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/3020-00-167-4208 **Body Style:** Plain, solid **Attachment Method:** Clamp Pitch Diameter: Between 0.7865 inches and 0.7875 inches **Teeth Quantity:** 63 **Bore Style:** Plain both ends **Outside Diameter:** 0.811 inches **Tooth Form:** Standard **Pressure Angle:** 20.0000 degrees Distance Between Body Face And Protruding Hub End: 0.313 inches first end **Face Width:** 0.062 inches **Bore Diameter:** 0.121 inches both ends **Hub Style Designator:** 1 step first end **End Length:** 0.298 inches first end **Precision Classification:** Quality number 10 or quality number 11 **End Diameter:** 0.186 inches first end First Step Length: 0.015 inches first end

First Step Diameter:

0.218 inches first end

Material:

Steel comp 303

**Material Specification:** 

Qq-s-764, type 303, cond a federal specification single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Mil-f-14072, finish e300 military specification single treatment response

## NSN 3020-00-167-4208

Spur Gear - Page 2 of 2



Style Designator:
Protruding hub
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
<b>Demilitarization:</b> No

Mil-std (military Standard):

Mil-f-14072 spec.