NSN 3020-00-168-4552

Sprocket Wheel - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/3020-00-168-4552

| Outside Diameter: |
|---|
| 1.668 inches |
| Overall Length: |
| 0.500 inches |
| Bore Diameter: |
| 0.500 inches |
| Bore Length: |
| 0.500 inches |
| Pitch Diameter: |
| 1.200 inches |
| Furnished Items And Quantity: |
| Setscrew, one each |
| Face Width: |
| 0.110 inches |
| Design Form: |
| Plain |
| Bore Type: |
| Straight |
| Counterbore Feature: |
| Not included |
| Keying Facility: |
| Not included |
| Securing Method: |
| Setscrew |
| Lightening Hole: |
| Not included |
| Protruding Hub Characteristic: |
| Plain |
| Securing Location: |
| Aa end |
| Belt/chain/film Size For Which Designed: |
| Roller chain |
| Roller Chain Pitch Type For Which Designed: |
| Single pitch |
| Teeth Row Quantity: |
| 1 |
| Teeth Quantity Per Row: |
| 15 |
| Asa Standard Chain Number: |
| 25 |
| Hardness Rating Test Method: |
| - |

Not rated

NSN 3020-00-168-4552 Sprocket Wheel - Page 2 of 2



| Bore Bearing: |
|---|
| Not included |
| Hub External Keyway: |
| Not included |
| Tooth Pitch: |
| 0.250 inches |
| Hub End Outside Diameter And Location: |
| 0.750 inches aa end |
| Distance From Outside Flange/rim To Hub End And Location: |
| 0.390 inches aa end |
| Material: |
| Steel, carbon |
| Material: |
| Steel |
| Surface Treatment: |
| Phosphate manganese |
| Style Designator: |
| Plain |
| Surface Treatment: |
| Phosphate, mil-p-16232, type m, class 2 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| T353-c |
| |
| |